


980nm 1W Chip

Introduction

980nm laser diode is packaged on standard C-Mount heat sink, or better heat sink ones, which also can be adopted in Medical Illumination, Target Indication, Laser Show, Scientific Research.



Parameters (25°C)

980nm 1W Chip			
Parameter		Unit	CLDM-0980-001W
Optical Parameter	Output Power P_o	mW	1000
	Center Wavelength λ_c	nm	980±10
	Beam Divergence $\theta_{\perp} \times \theta_{\parallel}$	deg	40x10
	COD	W	≥2.00
Chip Size	Emitting Area	μm	100
	Period	μm	500
	Cavity Length	μm	900
Electrical Parameter	Slope Efficiency E_s	W/A	≥ 0.90
	Threshold Current I_{th}	A	≤ 0.25
	Operating Current I_f	A	≤ 1.36
	Operating Voltage V_f	V	≤ 2.20





海特光电有限责任公司
Hi-Tech Optoelectronics Co.,Ltd.

Notice

1. Item notice: CLDM(item model)-****(center wavelength)-****(output power)
2. Data sheet is basis on the result of under 25°C testing.
3. Data sheet is basis on the C-Mount package testing.
4. For more information, please contact Hi-Tech Optoelectronics Co., Ltd.



Add: Shahe Industrial Park, Changping District, Beijing, China
Tel: +86-10-6076 9887 Fax: +86-10-6076 9887-699
Web: www.htoe.com.cn Email: sales@htoe.com.cn

